

# MAGNETIC SWEEPERS

## MAGNETIC FLOOR & SHOP SWEEPERS

**SS:** Works on hard floors or carpeted areas. Clean shops, offices, retail stores right up to the edge of walls, machinery into corners with its unique wheel design.

**FS/IS:** Ideal for floors, parking lots and construction sites (IS is Self Cleaning).



Magnet Width (in)	Overall Width (in)	Depth (in)	Height (in)	Wheel Diameter (in)	Clearance (in)	Hold (lbs)*	Weight (lbs)	Model No.
19	19-1/2	3	52	1-1/4	3/4	30	7.0	SS1800
12	16-1/2	5	48	6	1-3/4	80	11.0	FS1200
24	28-1/2	5	48	6	1-3/4	160	22.0	FS2400
36	40	5	48	6	1-3/4	240	31.0	FS3600
								IS1400
24	29-1/2	7-1/2	49-1/2	6	1-3/4	400	46.0	IS2400

**\*Note:** Sweepers are designed for attracting ferrous metal pieces and debris and are not designed for lifting heavy objects. The Hold rating is measured by a vertical pull test from a 0.5" thick ground steel plate for purpose of magnetic strength comparisons only.

## MAGNETIC SUSPENDED SWEEPERS



**YS:** Aluminum and stainless steel construction for outdoor use. Hang the sweeper from vehicles, utility equipment or skid-steers.

Magnet Wd. (in)	Overall Wd. (in)	Depth (in)	Height (in)	Hold (lbs)*	Weight (lbs)	Model No.
36	36-1/2	5	2-11/16	320	39.0	YS3600
48	48-1/2	5	2-11/16	426	52.0	YS4800
60	60-1/2	5	2-11/16	532	86.0	YS6000
84	84-1/2	5	2-11/16	745	91.0	YS8400

## ROAD/TOWABLE ELECTROMAGNETIC SWEEPERS



A towable electromagnetic sweeper design that is supplied with wheels, pneumatic tires, adjustable towbar, and parking stand. Stand folds up into the towbar when not in use. All units can be supplied with a heavy duty 115volt AC generator mounted to the top. Generators are powered by a 4 stroke OHV gasoline engine and are energized and de-energized using the 115 VAC "ON" - "OFF" switch on the generator. A remote switch on 20ft of cable is available upon request.

Sweeping Width (in)	Overall Width (in)	Depth (in)	Height (in)	Adjustable Ground Clearance (in)	Hold (lbs)	Weight (lbs)	Model No.
60	73	20	32	4-10		2600	RSE060
72	84	20	39	4-10		3000	RSE072
96	108	20	39	4-10		3500	RSE096
120	132	20	39	4-10		3900	RSE120

**\*Note:** Sweepers are designed for attracting ferrous metal pieces and debris and are not designed for lifting heavy objects. The Hold rating is measured by a vertical pull test from a 0.5" thick ground steel plate for purpose of magnetic strength comparisons only.